

**CONO 3 IP54**


Suspended IP54 LED luminaire.

|                                     |  |
|-------------------------------------|--|
| <b>Mounting:</b>                    | Suspended from the ceiling   |
| <b>Body material:</b>               | Aluminium, steel, stainless steel  |
| <b>Colour:</b>                      | Standard Black RAL 9005, other RAL colours on request ( please add RAL code after index number )                           |
| <b>LED module:</b>                  | Osram LED module included  |
| <b>Colour temperature:</b>          | 3000K or 4000K   |
| <b>Colour Rendering Index (CRI)</b> | >80 in standard  |
| <b>Driver:</b>                      | Electronic integrated driver in standard   |
| <b>Emergency unit:</b>              | N/A  |
| <b>Movement sensor:</b>             | N/A  |
| <b>Daylight control sensor:</b>     | N/A  |
| <b>Operating temperature range:</b> | minus 20°C ... +40°C   |
| <b>IP Class:</b>                    | IP54   |
| <b>Power:</b>                       | 220-240V 50/60Hz   |
| <b>Lighting direction:</b>          | Direct   |
| <b>Reflector type:</b>              | Aluminium white  |
| <b>Light distribution:</b>          | Symmetric  |
| <b>General data:</b>                | 5 Years standard warranty  |
|                                     | Different lumen output or wattage available on request   |
|                                     | All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist      |
|                                     | Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%. |
|                                     | System power consumption (LED module & driver) depends on components used  |



| Index no.     | Lumen output [lm] | Power [W] | Colour temp. [K] | CRI     | Lifetime [H] | Warranty [Years] | MacAdam [SDCM] | Weight [kg] |
|---------------|-------------------|-----------|------------------|---------|--------------|------------------|----------------|-------------|
| 5842.2500/830 | 2500              | 21        | 3000             | Ra > 80 | 50.000       | 5                | 3              | 2,00        |
| 5842.2500/840 | 2500              | 21        | 4000             | Ra > 80 | 50.000       | 5                | 3              | 2,00        |

