

## COIN WALL 2



Wall mounted IP54 LED luminaire.

<b>Mounting:</b>	Ceiling recessed, mounting brackets included
<b>Body material:</b>	Steel and aluminium
<b>Colour:</b>	Standard White RAL 9016, other RAL colours on request (please add RAL colour after index number)
<b>LED module:</b>	LED module included
<b>Colour temperature:</b>	3000K or 4000K
<b>Colour Rendering Index (CRI)</b>	>80 in standard, other on request
<b>Driver:</b>	Electronic Integrated driver
<b>Emergency unit:</b>	N/A
<b>Movement sensor:</b>	N/A
<b>Daylight control sensor:</b>	N/A
<b>Operating temperature range:</b>	0°C ... +40°C
<b>IP Class:</b>	IP54
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct lighting
<b>Reflector type:</b>	White
<b>Light distribution:</b>	Symmetric
<b>General data:</b>	5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%."



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6287.2400/830/24	2400	32	3000	Ra > 80	35.000	5	4	3,90
6287.2400/840/24	2400	32	4000	Ra > 80	35.000	5	4	3,90
6287.2400/830/40	2400	32	3000	Ra > 80	35.000	5	4	3,90
6287.2400/840/40	2400	32	4000	Ra > 80	35.000	5	4	3,90
6287.3600/830/24	3600	46	3000	Ra > 80	35.000	5	4	3,90
6287.3600/840/24	3600	46	4000	Ra > 80	35.000	5	4	3,90
6287.3600/830/40	3600	46	3000	Ra > 80	35.000	5	4	3,90
6287.3600/840/40	3600	46	4000	Ra > 80	35.000	5	4	3,90

