

FLAT PVS 600 LED PND


Pendant LED luminaire.

Mounting:	Suspended on 1,5m long steel wire suspension (with wire length control)
Body material:	Steel and aluminium
Colour:	Standard Gray, other RAL colours on request
LED module:	Vossloh Schwabe LED module included
Colour temperature:	3000K or 4000K
Colour Rendering Index (CRI)	>80 in standard
Driver:	Electronic driver in standard, DALI on request
Emergency unit:	On request - Standard or DALI 3 hour emergency unit
Movement sensor:	on request
Daylight control sensor:	on request
Operating temperature range:	0°C... +40°C
IP Class:	IP44
Power:	220-240V 50/60Hz
Lighting direction :	Direct lighting
Reflector type :	N/A
Light distribution :	Symmetric
Diffusor :	White PMMA Acrylic diffuser in standard, Microprismatic [MPR] on request
General data:	3 Years standard warranty

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6548.3000/830	3000	30	3000	Ra > 80	50.000	5	3	5,00
6548.3000/840	3000	30	4000	Ra > 80	50.000	5	3	5,00
UGR < 19								
6549.3300/830	3300	33	3000	Ra > 80	50.000	5	3	5,00
6549.3300/840	3300	33	4000	Ra > 80	50.000	5	3	5,00

