

BELL IP65



Suspended IP65 LED luminaire.

Mounting:	Suspended from the ceiling
Body material:	Aluminium, steel and acrylic tube
Colour:	Standard Gray RAL 9006, other RAL colours on request (please add RAL code after index number)
LED module:	Osram LED module included
Colour temperature:	3000K or 4000K
Colour Rendering Index (CRI):	>80 in standard
Driver:	Electronic integrated driver in standard
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	- 20°C ... +40°C
IP Class:	IP65
Power:	220-240V 50/60Hz
Lighting direction:	Direct
Reflector type:	Integrated lenses
Light distribution:	Symmetric
Reflector beam angle:	24° / 40°
General data:	5 Years standard warranty
	Different lumen output or wattage available on request
	All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
	Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.
	System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5843.1800/830/24D	1800	23	3000	Ra > 80	35.000	5	4	2,60
5843.1800/840/24D	1800	23	4000	Ra > 80	35.000	5	4	2,60
5843.1800/830/40D	1800	23	3000	Ra > 80	35.000	5	4	2,60
5843.1800/840/40D	1800	23	4000	Ra > 80	35.000	5	4	2,60

