

LINEAR AR



Ground mounted IP67 LED luminaire.

- Mounting:** On the ground
- Body material:** Aluminium and stainless steel
- Colour:** Standard Anthracite grey 7016, other RAL colours on request (please add RAL code after index number)
- LED module:** Philips / Osram or Tridonic LED module included
- Colour temperature:** 3000K, 4000K in standard, RGBW version on request
- Colour Rendering Index (CRI)** >80 in standard
- Driver:** Electronic driver, DALI or DMX on request
- Emergency unit:** N/A
- Movement sensor:** N/A
- Daylight control sensor:** N/A
- Operating temperature range:** - 20°C ... +40°C
- IP Class:** IP67
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting with possibility of light direction adjustment
- Reflector type:** Integrated lenses
- Light distribution:** Symmetric
- Diffuser:** Clear tempered glass in standard, mat on request
- General data:** 5 Years standard warranty

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Length [mm]	Weight [kg]
6588.3300/830	3300	22	3000	Ra > 80	50.000	5	3	890	2,50
6588.3300/840	3300	22	4000	Ra > 80	50.000	5	3	890	2,50
6588.4400/830	4400	29	3000	Ra > 80	50.000	5	3	1200	3,40
6588.4400/840	4400	29	4000	Ra > 80	50.000	5	3	1200	3,40

