

DLN 100 LED UP/DN


Wall mounted IP54 LED luminaire.

Mounting:	Directly on the wall
Body material:	Aluminium
Colour:	Standard White RAL 9016
LED module:	Standard Gray 9006, other RAL colours on request (please add RAL code after index number)
Colour temperature:	LED GU10 retrofit lamps included
Colour Rendering Index (CRI)	2700K, 3000K or 4000K available
Driver:	N/A
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	- 20°C ... +40°C
IP Class:	IP54
Power:	220-240V 50/60Hz
Lighting direction:	Direct / indirect
Reflector type:	
Light distribution:	Symmetric
Diffusor:	Clear glass
General data:	3 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3419.710/827/36D	710	9,2 W	2700	Ra > 80	15.000	3	4	1,40
3419.740/830/36D	740	9,2 W	3000	Ra > 80	15.000	3	4	1,40
3419.780/840/36D	780	9,2 W	4000	Ra > 80	15.000	3	4	1,40

