

PARKING FORTIMOR R

Recessed IP54 LED luminaire for installation in suspended ceilings.

- Mounting:** Ceiling recessed, mounting brackets included
- Body material:** Aluminium and steel
- Colour:** Standard Gray 9006, other RAL colours on request (please add RAL code after index number)
- LED module:** Philips / Osram or Tridonic LED module included
- Colour temperature:** 3000K or 4000K
- Colour Rendering Index (CRI):** >80 in standard other on request
- Driver:** On request
- Emergency unit:** On request
- Movement sensor:** N/A
- Daylight control sensor:** N/A
- Operating temperature range:** -20°C ... +40°C
- IP Class:** IP54
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting
- Reflector type:** Aluminium white
- Light distribution:** Symmetric
- Diffuser:** Mat glass in standard, other on request
- General data:** 5 Years standard warranty



Different lumen output or wattage available on request


All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Length [mm]	Weight [kg]
5722.4400/830	4400	29	3000	Ra > 80	50.000	5	3	1216	4,50
5722.4400/840	4400	29	4000	Ra > 80	50.000	5	3	1216	4,50
5722.5500/830	5500	36	3000	Ra > 80	50.000	5	3	1500	5,80
5722.5500/840	5500	36	4000	Ra > 80	50.000	5	3	1500	5,80



110x1185