

**CLINICA BED IP54**



Wall mounted IP54 LED luminaire

|                                     |  |
|-------------------------------------|--|
| <b>Mounting:</b>                    | Wall mounted   |
| <b>Body material:</b>               | Steel and aluminium  |
| <b>Colour:</b>                      | Standard White RAL 9016, other RAL colours on request (please add RAL colour after index number)   |
| <b>LED module:</b>                  | LED module included  |
| <b>Colour temperature:</b>          | 3000K or 4000K   |
| <b>Colour Rendering Index (CRI)</b> | >80 in standard, other on request  |
| <b>Driver:</b>                      | Electronic Integrated driver   |
| <b>Emergency unit:</b>              | N/A  |
| <b>Movement sensor:</b>             | N/A  |
| <b>Daylight control sensor:</b>     | N/A  |
| <b>Operating temperature range:</b> | 0°C ... +40°C  |
| <b>IP Class:</b>                    | IP54   |
| <b>Power:</b>                       | 220-240V 50/60Hz   |
| <b>Lighting direction:</b>          | Direct/indirect  |
| <b>Reflector type:</b>              | White  |
| <b>Light distribution:</b>          | Symmetric  |
| <b>Diffuser:</b>                    | White PMMA Acrylic diffuser in standard [WD], clear [CG] or frosted glass [FG] Microprismatic [MPR] or any other on request  |
| <b>General data:</b>                | 5 Years standard warranty<br>Different lumen output or wattage available on request<br><br>All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist<br><br>Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%." |



| Index no.        | Lumen output [lm] | Power [W] | Colour temp. [K] | CRI     | Lifetime [H] | Warranty [Years] | MacAdam [SDCM] | Weight [kg] |
|------------------|-------------------|-----------|------------------|---------|--------------|------------------|----------------|-------------|
| 6587.UD.6600/830 | 6600              | 44        | 3000             | Ra > 80 | 50.000       | 5                | 3              | 5,00        |
| 6587.UD.6600/840 | 6600              | 44        | 4000             | Ra > 80 | 50.000       | 5                | 3              | 5,00        |

