


PROFI TEC5 OP LED LINE




Available versions




Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Length [mm]	Weight [kg]
3506.4400/830	4400	29	3000	Ra > 80	50.000	5	3	1250	3,20
3506.4400/840	4400	29	4000	Ra > 80	50.000	5	3	1250	3,20
3506.8000/830	8000	54	3000	Ra > 80	50.000	5	3	1250	3,20
3506.8000/840	8000	54	4000	Ra > 80	50.000	5	3	1250	3,20
PENDANT									
3506.PND.4400/830	4400	29	3000	Ra > 80	50.000	5	3	1250	3,20
3506.PND.4400/840	4400	29	4000	Ra > 80	50.000	5	3	1250	3,20
3506.PND.8000/830	8000	54	3000	Ra > 80	50.000	5	3	1250	3,20
3506.PND.8000/840	8000	54	4000	Ra > 80	50.000	5	3	1250	3,20
PENDANT UP/DN									
3506.UD.8800/830	8800	58	3000	Ra > 80	50.000	5	3	1250	3,20
3506.UD.8800/840	8800	58	4000	Ra > 80	50.000	5	3	1250	3,20
3506.UD.12400/830	12400	83	3000	Ra > 80	50.000	5	3	1250	3,20
3506.UD.12400/840	12400	83	4000	Ra > 80	50.000	5	3	1250	3,20


[WD] diffuser



[AC] diffuser



[MPR] diffuser



Surface mounted or Suspended LED luminaire with direct or direct / indirect lighting.

Mounting:

Directly on the ceiling - index nr. 3506.XXXX
Suspended - index nr. 3506.PND.XXXX, suspension wires included
Suspended direct / indirect - index nr. 3506.UD.XXXX, suspension wires included

Body material:

Aluminium profile

Colour:

Standard Gray 9006, other RAL colours on request (please add RAL code after index number)

LED module:

Philips / Osram or Tridonic LED module included

Colour temperature:

3000K or 4000K

Colour Rendering Index (CRI)

>80 in standard, other on request

Driver:

Electronic driver in standard, DALI on request

Emergency unit:

on request - Standard or DALI 3 hour emergency unit

Movement sensor:

on request

Daylight control sensor:

on request

Operating temperature range:

0°C ... +40°C

IP Class:

IP20 in standard, IP44 on request

Power:

220-240V 50/60Hz

Lighting direction:

Direct index nr. 3506.XXXX or Direct / indirect - index nr. 3506.UD.XXXX

Reflector type:

Aluminium white

Light distribution:

Symmetric

Diffuser:

White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request.

General data:

5 Years standard warranty

UGR<19 diffuser on request

Luminaires can be connected into long lighting lines

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

