

**RONI LED**



Wall mounted IP65 LED luminaire.

<b>Mounting:</b>	Directly on the wall
<b>Body material:</b>	Aluminium
<b>Colour:</b>	Standard Dark Gray 7016, other RAL colours on request ( please add RAL code after index number )
<b>LED module:</b>	Osram LED module included
<b>Colour temperature:</b>	3000K or 4000K
<b>Colour Rendering Index (CRI):</b>	>80 in standard
<b>Driver:</b>	Electronic integrated driver
<b>Emergency unit:</b>	N/A
<b>Movement sensor:</b>	N/A
<b>Daylight control sensor:</b>	N/A
<b>Operating temperature range:</b>	- 20°C ... +40°C
<b>IP Class:</b>	IP65
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct
<b>Reflector type:</b>	N/A
<b>Light distribution:</b>	Symmetric
<b>Diffusor:</b>	PMMA White diffusor
<b>General data:</b>	5 Years standard warranty

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
4128.1500/830	1500	13	3000	Ra > 80	50.000	5	3	1,80
4128.1500/840	1500	13	4000	Ra > 80	50.000	5	3	1,80

