

PROFI TEC5 IND LED LINE



Suspended, indirect lighting LED luminaire.

- Mounting:** Suspended, suspension wires included
- Body material:** Aluminium profile
- Colour:** Standard Gray 9006, other RAL colours on request (please add RAL code after index number)
- LED module:** Philips / Osram or Tridonic LED module included
- Colour temperature:** 3000K or 4000K
- Colour Rendering Index (CRI)** >80 in standard, other on request
- Driver:** Electronic driver in standard, DALI on request
- Emergency unit:** on request - Standard or DALI 3 hour emergency unit
- Movement sensor:** on request
- Daylight control sensor:** on request
- Operating temperature range:** 0°C... +40°C
- IP Class:** IP20 in standard, IP44 on request
- Power:** 220-240V 50/60Hz
- Lighting direction:** Indirect
- Reflector type:** N/A
- Light distribution:** Symmetric
- Diffuser:** Clear acrylic
- General data:** 5 Years standard warranty

Luminaires can be connected into long lighting lines

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Length [mm]	Weight [kg]
3507.4400/830	4400	29	3000	Ra > 80	50.000	5	3	1250	3,20
3507.4400/840	4400	29	4000	Ra > 80	50.000	5	3	1250	3,20
3507.8000/830	8000	54	3000	Ra > 80	50.000	5	3	1250	3,20
3507.8000/840	8000	54	4000	Ra > 80	50.000	5	3	1250	3,20

Available versions

