

**UNO SURF AR LED LV**


Surface mounted LED luminaire.

<b>Mounting:</b>	Directly on the ceiling
<b>Body material:</b>	Steel and aluminium
<b>Colour:</b>	Standard Gray RAL 9006, other RAL colours on request (please add RAL colour after index number)
<b>LED module:</b>	LED AR111 retrofit lamp included
<b>Colour temperature:</b>	2700K or 3000K
<b>Colour Rendering Index (CRI)</b>	>80 in standard, other on request
<b>Driver:</b>	N/A
<b>Emergency unit:</b>	N/A
<b>Movement sensor:</b>	N/A
<b>Daylight control sensor:</b>	N/A
<b>Operating temperature range:</b>	0°C ... +40°C
<b>IP Class:</b>	IP20
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct lighting
<b>Light distribution:</b>	Symmetric
<b>Beam angle:</b>	24° / 40°
<b>General data:</b>	3 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux &amp; Luminaire Power tolerance +/- 10%.

IP20

 220-240 V  
50-60 Hz


Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3540.610/827/24D	610	10	2700	Ra > 80	40.000	3	3	1,50
3540.610/830/40D	610	10	3000	Ra > 80	40.000	3	3	1,50
3540.800/827/24D	800	15	2700	Ra > 80	40.000	3	3	1,50
3540.760/827/40D	760	15	2700	Ra > 80	40.000	3	3	1,50

