

**FANTOM CURVE LED PND**

Pendant LED luminaire.

- Mounting:** Suspended on 1,5m long steel wire suspension ( with wire length control )
- Body material:** Steel and aluminium
- Colour:** Standard Gray 9006, other RAL colours on request ( please add RAL code after index number )
- LED module:** Philips, Osram or Tridonic LED module included
- Colour temperature:** 3000K or 4000K
- Colour Rendering Index (CRI):** >80 in standard
- Driver:** Electronic driver in standard, DALI on request
- Emergency unit:** On request - Standard or DALI 3 hour emergency unit
- Movement sensor:** on request
- Daylight control sensor:** on request
- Operating temperature range:** 0°C ... +40°C
- IP Class:** IP20 in standard, IP44 on request
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting
- Reflector type:** Aluminium white
- Light distribution:** Symmetric
- Diffuser:** White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request.
- General data:** 5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



| Index no.     | Lumen output [lm] | Power [W] | Colour temp. [K] | CRI     | Lifetime [H] | Warranty [Years] | MacAdam [SDCM] | Weight [kg] |
|---------------|-------------------|-----------|------------------|---------|--------------|------------------|----------------|-------------|
| 6137.4400/830 | 4400              | 29        | 3000             | Ra > 80 | 50.000       | 5                | 3              | 4,50        |
| 6137.4400/840 | 4400              | 29        | 4000             | Ra > 80 | 50.000       | 5                | 3              | 4,50        |

