

ELP LED IP65



Surface mounted IP65 LED luminaire.

Mounting:	Directly on the ceiling
Body material:	Aluminium and steel
Colour:	Standard White RAL 9016, other RAL colours on request (please add RAL code after index number)
LED module:	Philips / Osram / Tridonic or equivalent LED module included
Colour temperature:	3000K or 4000K
Colour Rendering Index (CRI):	>80 in standard
Driver:	Electronic driver in standard, DALI on request
Emergency unit:	on request - Standard or DALI 3 hour emergency unit
Movement sensor:	on request
Daylight control sensor:	N/A
Operating temperature range:	- 20°C ... +40°C
IP Class:	IP65
Power:	220-240V 50/60Hz
Lighting direction:	Direct
Reflector type:	Aluminium white
Light distribution:	Symmetric
Diffuser:	White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request.
General data:	5 Years standard warranty
	Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
4086.11000/830	11000	70	3000	Ra > 80	50.000	5	3	5,00
4086.11000/840	11000	70	4000	Ra > 80	50.000	5	3	5,00
4086.20000/830	20000	125	3000	Ra > 80	50.000	5	3	5,00
4086.20000/840	20000	125	4000	Ra > 80	50.000	5	3	5,00

