

## ARM LED



Free standing desk LED luminaire

<b>Mounting:</b>	Free standing
<b>Body material:</b>	Steel and aluminium
<b>Colour:</b>	Standard Gray 9006, other RAL colours on request ( please add RAL code after index number )
<b>LED module:</b>	Philips, Osram or Tridonic or equivalent LED module
<b>Colour temperature:</b>	3000K or 4000K
<b>Colour Rendering Index (CRI)</b>	>80 in standard, other on request
<b>Driver:</b>	Electronic integrated driver
<b>Emergency unit:</b>	N/A
<b>Movement sensor:</b>	N/A
<b>Daylight control sensor:</b>	N/A
<b>Operating temperature range:</b>	0°C ... +40°C
<b>IP Class:</b>	IP20 in standard
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct lighting with possibility of light direction adjustment
<b>Reflector type:</b>	Aluminium white
<b>Light distribution:</b>	Symmetric
<b>General data:</b>	5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

IP20

220-240 V

50-60 Hz



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6087.1100/830	1100	10	3000	Ra > 80	50.000	5	3	5,50
6087.1100/840	1100	10	4000	Ra > 80	50.000	5	3	5,50

