

**DAMARIS COIN**



LED spotlight for three - phase track systems.

- Mounting:** Directly in 3 phase track
- Body material:** Steel and aluminium
- Colour:** Standard Gray RAL 9006, other RAL colours on request ( please add RAL code after index number )
- LED module:** Osram LED module included
- Colour temperature:** 3000K or 4000K
- Colour Rendering Index (CRI):** >80 in standard
- Driver:** Electronic integrated driver
- Emergency unit:** N/A
- Movement sensor:** N/A
- Daylight control sensor:** N/A
- Operating temperature range:** 0°C ... +40°C
- IP Class:** IP20
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting with possibility of light direction adjustment
- Reflector type:** Integrated lens
- Light distribution:** Symmetric
- Reflector beam angle:** 24° / 40°
- Diffuser:** N/A
- General data:** 5 Years standard warranty, possible extension with project registration

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Ceiling mounting base instead of Track Adaptor available on request

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6508.1800/830/24D	1800	23	3000	Ra > 80	50.000	5	3	1,50
6508.1800/840/24D	1800	23	4000	Ra > 80	50.000	5	3	1,50
6508.1800/830/40D	1800	23	3000	Ra > 80	50.000	5	3	1,50
6508.1800/840/40D	1800	23	4000	Ra > 80	50.000	5	3	1,50

