


LWN AP 3 PL



Recessed LED luminaire for installation in modular suspended ceilings, version for gypsum ceiling on request.

- Mounting:** Modular ceiling lay in type in standard, mounting brackets for gypsum ceiling on request.
- Body material:** Steel and aluminium
- Colour:** Standard White RAL 9016, other RAL colours on request (please add RAL colour after index number)
- LED module:** Philips / Osram or Tridonic LED module included
- Colour temperature:** 3000K or 4000K
- Colour Rendering Index (CRI):** >80 in standard, >90 on request
- Driver:** Electronic driver in standard, DALI on request
- Emergency unit:** On request - Standard or DALI 3 hour emergency unit
- Movement sensor:** on request
- Daylight control sensor:** on request
- Operating temperature range:** 0°C ... +40°C
- IP Class:** IP20
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting
- Reflector type:** Aluminium glossy or mat
- Light distribution:** Symmetric
- Diffuser:** Aluminium mat louvers
- General data:** 5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6068.6600/830	6600	44	3000	Ra > 80	50.000	5	3	6,20
6068.6600/840	6600	44	4000	Ra > 80	50.000	5	3	6,20

