

STAR LED SPOT



LED spotlight for three - phase track systems.

Mounting:	Directly in 3 phase track
Body material:	Steel and aluminium
Colour:	Standard Gray RAL 9006, other RAL colours on request (please add RAL code after index number)
LED module:	Philips LED module included
Colour temperature:	3000K or 4000K available
Colour Rendering Index (CRI):	>80 or >90 in standard
Driver:	Electronic integrated driver
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	0°C ... +40°C
IP Class:	IP20
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting with possibility of light direction adjustment
Reflector type:	Aluminium glossy
Light distribution:	Symmetric
Reflector beam angle:	16° / 24° / 36° / 54°
General data:	5 Years standard warranty

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Ceiling mounting base instead of Track Adaptor available on request

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5391.1100/830PW	1100	12	3000	Ra > 80	50.000	5	3	1,40
5391.1100/930PW	1100	12	3000	Ra > 90	50.000	5	3	1,40
5391.1100/840	1100	11	4000	Ra > 80	50.000	5	3	1,40
5391.2000/830PW	2000	22	3000	Ra > 80	50.000	5	3	1,40
5391.2000/930PW	2000	22	3000	Ra > 90	50.000	5	3	1,40
5391.2000/840	2000	19	4000	Ra > 80	50.000	5	3	1,40
5391.3000/830PW	3000	27	3000	Ra > 80	50.000	5	3	1,40
5391.3000/930PW	3000	27	3000	Ra > 90	50.000	5	3	1,40
5391.3000/840	3000	27	4000	Ra > 80	50.000	5	3	1,40

