

## DL 185 GAR LED



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
4020.1100/827	1100	9	2700	Ra > 80	50.000	5	3	1,75
4020.1100/830	1100	9	3000	Ra > 80	50.000	5	3	1,75
4020.1100/840	1100	9	4000	Ra > 80	50.000	5	3	1,75
4020.2400/827	2400	20	2700	Ra > 80	50.000	5	3	1,75
4020.2400/830	2400	20	3000	Ra > 80	50.000	5	3	1,75
4020.2400/840	2400	20	4000	Ra > 80	50.000	5	3	1,75
4020.3200/827	3200	28	2700	Ra > 80	50.000	5	3	1,75
4020.3200/830	3200	28	3000	Ra > 80	50.000	5	3	1,75
4020.3200/840	3200	28	4000	Ra > 80	50.000	5	3	1,75
4020.1100/927	1100	11	2700	Ra > 90	50.000	5	3	1,75
4020.1100/930	1100	11	3000	Ra > 90	50.000	5	3	1,75
4020.1100/940	1100	11	4000	Ra > 90	50.000	5	3	1,75
4020.2000/927	2000	20	2700	Ra > 90	50.000	5	3	1,75
4020.2000/930	2000	20	3000	Ra > 90	50.000	5	3	1,75
4020.2000/940	2000	20	4000	Ra > 90	50.000	5	3	1,75
4020.3000/927	3000	32	2700	Ra > 90	50.000	5	3	1,75
4020.3000/930	3000	32	3000	Ra > 90	50.000	5	3	1,75
4020.3000/940	3000	32	4000	Ra > 90	50.000	5	3	1,75
4020.3000/930CW	3000	36	3000	Ra > 90	50.000	5	3	1,75
4020.2600/925FW	2600	35	2500	Ra > 90	50.000	5	3	1,75
4020.2600/930FR	2600	35	3000	Ra > 90	50.000	5	3	1,75



Recessed LED downlight for installation in suspended ceilings.

<b>Mounting:</b>	Ceiling recessed, mounting brackets included
<b>Body material:</b>	Steel and aluminium
<b>Colour:</b>	Standard Gray RAL 9006, other RAL colours on request (please add RAL colour after index number)
<b>LED module:</b>	Philips / Osram or Tridonic LED module included
<b>Colour temperature:</b>	2700K, 3000K or 4000K available
<b>Colour Rendering Index (CRI)</b>	>80 or >90 in standard
<b>Driver:</b>	Electronic driver in standard, DALI or 1-10V Analogue on request
<b>Emergency unit:</b>	On request - Standard or DALI 3 hour emergency unit
<b>Movement sensor:</b>	N/A
<b>Daylight control sensor:</b>	N/A
<b>Operating temperature range:</b>	0°C... +40°C
<b>IP Class:</b>	IP20 in standard, IP44 on request
<b>Power:</b>	220-240V 50/60Hz
<b>Lighting direction:</b>	Direct lighting
<b>Reflector type:</b>	Aluminium glossy
<b>Light distribution:</b>	Symmetric
<b>Reflector beam angle:</b>	16° / 24° / 36° / 54°
<b>Diffuser:</b>	Clear or frosted glass on request
<b>General data:</b>	5 Years standard warranty, possible extension with project registration
	Different lumen output or wattage available on request
	Product is also available with special application LED modules: Premium Color, CrispWhite, Food WarmWhite, Food PremiumRed and many others - details on request
	All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
	Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.
	System power consumption (LED module & driver) depends on components used

