

## DLK 130 LED DISC



Recessed LED downlight for installation in suspended ceilings.

- Mounting:** Ceiling recessed, mounting brackets included
- Body material:** Steel and aluminium
- Colour:** Standard White RAL 9016, other RAL colours on request (please add RAL colour after index number)a
- LED module:** Philips / Osram / Tridonic or equivalent LED module included
- Colour temperature:** 2700K, 3000K or 4000K available
- Colour Rendering Index (CRI)** >80
- Driver:** Electronic integrated driver in standard
- Emergency unit:** N/A
- Movement sensor:** N/A
- Daylight control sensor:** N/A
- Operating temperature range:** 0°C ... +40°C
- IP Class:** IP44
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting with possibility of light direction adjustment
- Reflector type:** White
- Light distribution:** Symmetric
- Diffuser:** Miropismatic in standard
- General data:** 5 years standard warranty

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
4282.800/827	800	10	2700	Ra > 80	50.000	5	3	0,60
4282.800/830	800	10	3000	Ra > 80	50.000	5	3	0,60
4282.800/840	800	10	4000	Ra > 80	50.000	5	3	0,60

