


SATURN 900 LED SURF



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5673.8800/830	8800	60	3000	Ra > 80	50.000	5	3	10,50
5673.8800/840	8800	60	4000	Ra > 80	50.000	5	3	10,50



Surface mounted LED luminaire.

- Mounting:

Body material:

Colour:

LED module:

Colour temperature:

Colour Rendering Index (CRI)

Driver:

Emergency unit:

Movement sensor:

Daylight control sensor:

Operating temperature range:

IP Class:

Power:

Lighting direction:

Reflector type:

Light distribution:

Diffuser:

General data:
- Directly on the ceiling

Steel and aluminium

Standard Gray RAL 9006, other RAL colours on request (please add RAL colour after index number)

Philips / Osram or Tridonic LED module included

3000K or 4000K

>80 in standard

Electronic driver in standard, DALI on request

N/A

N/A

N/A

0°C ... +40°C

IP20 in standard, IP44 on request

220-240V 50/60Hz

Direct lighting

Aluminium white

Symmetric

White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request.

5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used