

HERON



Outdoor IP65 LED luminaire.

- Mounting:** On circular pole (not included)
- Body material:** Aluminium
- Colour:** Standard gray RAL 9006, other RAL colours on request (please add RAL code after index number)
- LED module:** Philips, Osram or Tridonic LED module included
- Colour temperature:** 3000K, 4000K or 5700K
- Colour Rendering Index (CRI)** >80 in standard
- Driver:** Electronic driver
- Emergency unit:** N/A
- Movement sensor:** N/A
- Daylight control sensor:** N/A
- Operating temperature range:** - 20°C ... +40°C
- IP Class:** IP65
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting
- Reflector type:** Integrated lenses
- Light distribution:** Symmetric in standard, asymmetric on request
- Diffusor:** Clear glass, other on request
- General data:** 5 Years standard warranty

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
4971.11000/730	11000	81	3000	Ra > 70	50.000	5	4	12,00
4971.11000/740	11000	81	4000	Ra > 70	50.000	5	4	12,00
4971.11000/757	11000	81	5700	Ra > 70	50.000	5	4	12,00
4971.14500/730	14500	107	3000	Ra > 70	50.000	5	4	12,00
4971.14500/740	14500	107	4000	Ra > 70	50.000	5	4	12,00
4971.14500/757	14500	107	5700	Ra > 70	50.000	5	4	12,00
4971.17200/730	17200	132	3000	Ra > 70	50.000	5	4	12,00
4971.17200/740	17200	132	4000	Ra > 70	50.000	5	4	12,00
4971.17200/757	17200	132	5700	Ra > 70	50.000	5	4	12,00

