

GLO SPOT MINI


LED spotlight for three - phase track systems.

| | |
|--------------------------------------|---|
| Mounting: | Directly in 3 phase track |
| Body material: | Steel and aluminium |
| Colour: | Standard Gray RAL 9006, other RAL colours on request (please add RAL code after index number) |
| LED module: | Philips / Osram or Tridonic LED module included |
| Colour temperature: | 2700K, 3000K or 4000K |
| Colour Rendering Index (CRI): | >80 or >90 in standard |
| Driver: | Electronic driver in standard |
| Emergency unit: | N/A |
| Movement sensor: | N/A |
| Daylight control sensor: | N/A |
| Operating temperature range: | 0°C ... +40°C |
| IP Class: | IP20 |
| Power: | 220-240V 50/60Hz |
| Lighting direction: | Direct lighting with possibility of light direction adjustment |
| Reflector type: | Aluminium glossy |
| Light distribution: | Symmetric |
| Reflector beam angle: | 24° / 40° |
| Diffuser: | Clear glass |
| General data: | 5 Years standard warranty, possible extension with project registration |

Different lumen output or wattage available on request

All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Ceiling mounting base instead of Track Adaptor available on request

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



| Index no. | Lumen output [lm] | Power [W] | Colour temp. [K] | CRI | Lifetime [H] | Warranty [Years] | MacAdam [SDCM] | Weight [kg] |
|---------------|-------------------|-----------|------------------|---------|--------------|------------------|----------------|-------------|
| 5881.2400/827 | 2400 | 20 | 2700 | Ra > 80 | 50.000 | 5 | 3 | 1,40 |
| 5881.2400/830 | 2400 | 20 | 3000 | Ra > 80 | 50.000 | 5 | 3 | 1,40 |
| 5881.2400/840 | 2400 | 20 | 4000 | Ra > 80 | 50.000 | 5 | 3 | 1,40 |
| 5881.3200/827 | 3200 | 28 | 2700 | Ra > 80 | 50.000 | 5 | 3 | 1,40 |
| 5881.3200/830 | 3200 | 28 | 3000 | Ra > 80 | 50.000 | 5 | 3 | 1,40 |
| 5881.3200/840 | 3200 | 28 | 4000 | Ra > 80 | 50.000 | 5 | 3 | 1,40 |
| 5881.4500/830 | 4500 | 34 | 3000 | Ra > 80 | 50.000 | 5 | 3 | 1,40 |
| 5881.4500/840 | 4500 | 34 | 4000 | Ra > 80 | 50.000 | 5 | 3 | 1,40 |
| 5881.2000/927 | 2000 | 20 | 2700 | Ra > 90 | 50.000 | 5 | 3 | 1,40 |
| 5881.2000/930 | 2000 | 20 | 3000 | Ra > 90 | 50.000 | 5 | 3 | 1,40 |
| 5881.2000/940 | 2000 | 20 | 4000 | Ra > 90 | 50.000 | 5 | 3 | 1,40 |
| 5881.3000/927 | 3000 | 32 | 2700 | Ra > 90 | 50.000 | 5 | 3 | 1,40 |
| 5881.3000/930 | 3000 | 32 | 3000 | Ra > 90 | 50.000 | 5 | 3 | 1,40 |
| 5881.3000/940 | 3000 | 32 | 4000 | Ra > 90 | 50.000 | 5 | 3 | 1,40 |
| 5881.4000/927 | 4000 | 34 | 2700 | Ra > 90 | 50.000 | 5 | 3 | 1,40 |
| 5881.4000/930 | 4000 | 34 | 3000 | Ra > 90 | 50.000 | 5 | 3 | 1,40 |
| 5881.4000/940 | 4000 | 34 | 4000 | Ra > 90 | 50.000 | 5 | 3 | 1,40 |

