

KING SIZE PND LED



Pendant LED luminaire

Mounting:	Suspended on 1,5m long steel wire suspension (with wire length control)
Body material:	Steel, aluminium, acrylic tube
Colour:	Standard White RAL 9016, other RAL colours on request (please add RAL code after index number)
LED module:	Philips MASTER LEDtube retrofit LED lamp
Colour temperature:	3000K, 4000K or 6500K
Colour Rendering Index (CRI):	>80 in standard
Driver:	N/A
Emergency unit:	N/A
Movement sensor:	N/A
Daylight control sensor:	N/A
Operating temperature range:	0°C... +40°C
IP Class:	IP20
Power:	220-240V 50/60Hz
Lighting direction:	Direct lighting
Reflector type:	N/A
Light distribution:	Symmetric
General data:	5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lum maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Length [mm]	Weight [kg]
5218.2300/830	2300	16	3000K	Ra > 80	50.000	5	3	1296	2,00
5218.2500/840	2500	16	4000K	Ra > 80	50.000	5	3	1296	2,00
5218.2500/865	2500	16	6500K	Ra > 80	50.000	5	3	1296	2,00
5218.3500/830	3500	24	3000K	Ra > 80	50.000	5	3	1596	3,00
5218.3700/840	3700	24	4000K	Ra > 80	50.000	5	3	1596	3,00
5218.3700/865	3700	24	6500K	Ra > 80	50.000	5	3	1596	3,00

