

WP BAR IP65



Surface mounted IP65 LED luminaire.

Mounting:	Directly on the ceiling
Body material:	Polycarbonate
Colour:	Standard Gray , white diffusor
LED module:	Philips / Osram / Tridonic or equivalent LED module included
Colour temperature:	3000K or 4000K
Colour Rendering Index (CRI)	>80 in standard
Driver:	Electronic integrated driver in standard
Emergency unit:	On request
Movement sensor:	On request
Daylight control sensor:	On request
Operating temperature range:	- 20°C ... +40°C
IP Class:	IP65
Power:	220-240V 50/60Hz
Lighting direction:	Direct
Reflector type:	Aluminium white
Light distribution:	Symmetric
General data:	5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

IP65 220-240 V 50-60 Hz



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6220.4000/830	4000	38	3000	Ra > 80	50.000	3	4	1,70
6220.4000/840	4000	38	4000	Ra > 80	50.000	3	4	1,70
6220.6000/830	6000	60	3000	Ra > 80	50.000	3	4	1,70
6220.6000/840	6000	60	4000	Ra > 80	50.000	3	4	1,70

