

**FLEXLIGHT LED 4**



Surface mounted IP54 LED luminaire.

- Mounting:** Directly on the ceiling
- Body material:** Aluminium and steel
- Colour:** Standard White RAL 9016, other RAL colours on request ( please add RAL code after index number )
- LED module:** Philips / Osram / Tridonic or equivalent LED module included
- Colour temperature:** 3000K or 4000K
- Colour Rendering Index (CRI)** >80 in standard
- Driver:** Electronic driver in standard, DALI on request
- Emergency unit:** on request - Standard or DALI 3 hour emergency unit
- Movement sensor:** on request
- Daylight control sensor:** N/A
- Operating temperature range:** - 20°C ... +40°C
- IP Class:** IP54
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct
- Reflector type:** Aluminium glossy
- Light distribution:** Symmetric
- Diffuser:** Clear glass, mat glass or any other on request
- General data:** 5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
4525.10000/830	10000	73	3000	Ra > 80	50.000	5	3	12,00
4525.10000/840	10000	73	4000	Ra > 80	50.000	5	3	12,00

