


PROFI 40 LED

Surface mounted or Suspended LED luminaire with direct or direct / indirect lighting.

Mounting:	Directly on the ceiling - index nr. 6248.XXXX Suspended - standard 1,5 m long steel suspension wires to be ordered separately - two pieces per single luminaire needed
Body material:	Aluminium profile
Colour:	Standard Gray 9006, other RAL colours on request (please add RAL code after index number)
LED module:	Philips / Osram or Tridonic LED module included
Colour temperature:	3000K or 4000K
Colour Rendering Index (CRI)	>80 in standard, other on request
Driver:	Electronic driver in standard, DALI on request
Emergency unit:	on request - Standard or DALI 3 hour emergency unit
Movement sensor:	on request
Daylight control sensor:	on request
Operating temperature range:	0°C... +40°C
IP Class:	IP20 in standard, IP44 on request
Power:	220-240V 50/60Hz
Lighting direction:	Direct index nr. 6248.XXXX or Direct / indirect - index nr. 6248.UD.XXXX
Reflector type:	Aluminium white
Light distribution:	Symmetric
Diffuser:	White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request.
General data:	5 Years standard warranty UGR<19 diffuser on request



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Length [mm]	Weight [kg]
SURFACE MOUNTED									
6248.3300/830	3300	23	3000	Ra > 80	50.000	5	3	868	2,00
6248.3300/840	3300	23	4000	Ra > 80	50.000	5	3	868	2,00
6248.4400/830	4400	29	3000	Ra > 80	50.000	5	3	1149	2,50
6248.4400/840	4400	29	4000	Ra > 80	50.000	5	3	1149	2,50
6248.5500/830	5500	36	3000	Ra > 80	50.000	5	3	1430	3,00
6248.5500/840	5500	36	4000	Ra > 80	50.000	5	3	1430	3,00
SUSPENDED UP/DN									
6248.UD.6600/830	6600	44	3000	Ra > 80	50.000	5	3	1149	3,00
6248.UD.6600/840	6600	44	4000	Ra > 80	50.000	5	3	1149	3,00
6248.UD.8800/830	8800	58	3000	Ra > 80	50.000	5	3	1430	3,50
6248.UD.8800/840	8800	58	4000	Ra > 80	50.000	5	3	1430	3,50



Luminaires can be connected into long lighting lines

Different lumen output or wattage available on request


All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.


System power consumption (LED module & driver) depends on components used

PROFI 40 LED

Available versions



Accessories



6247.15



6564.15

UP/DN version




Index no.

Steel wire suspension


6247.15 single 1,5 m long suspension set for PROFI luminaire - 2 pcs. Per luminaire needed.

6564.15 1,5 m long transparent power cable with ceiling base and terminal block

[WD] diffuser



[AC] diffuser



[MPR] diffuser

