

BED FLEX



Wall mounted, adjustable LED luminaire

| | |
|--------------------------------------|--|
| Mounting: | Wall mounted |
| Body material: | Steel and aluminium |
| Colour: | Standard White 9010, other RAL colours on request (please add RAL code after index number) |
| LED module: | Philips / Osram or Tridonic LED module included |
| Colour temperature: | 2700K, 3000K or 4000K available |
| Colour Rendering Index (CRI): | >80 in standard, other on request |
| Driver: | Electronic driver |
| Emergency unit: | N/A |
| Movement sensor: | N/A |
| Daylight control sensor: | N/A |
| Operating temperature range: | 0°C ... +40°C |
| IP Class: | IP20 in standard |
| Power: | 220-240V 50/60Hz |
| Lighting direction: | Direct lighting with possibility of light direction adjustment |
| Reflector type: | Integrated lens |
| Light distribution: | Symmetric |
| General data: | 5 Years standard warranty |

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

IP20
220-240 V
50-60 Hz



| Index no. | Lumen output [lm] | Power [W] | Colour temp. [K] | CRI | Lifetime [H] | Warranty [Years] | MacAdam [SDCM] | Weight [kg] |
|--------------|-------------------|-----------|------------------|---------|--------------|------------------|----------------|-------------|
| 6514.300/830 | 210 | 3 | 3000 | Ra > 80 | 30.000 | 3 | 3 | 0,40 |
| 6514.300/840 | 210 | 3 | 4000 | Ra > 80 | 30.000 | 3 | 3 | 0,40 |

