

## **DLN 90 LED WALL**





Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
4807.800/827	800	10	2700	Ra > 80	50.000	5	3	0,80
4807.800/830	800	10	3000	Ra > 80	50.000	5	3	0,80
4807.800/840	800	10	4000	Ra > 80	50.000	5	3	0.80

Wall mounted LED luminaire

Wall mounted Mounting: Body material: Steel and aluminium

Standard Gray 9006, other RAL Colour: colours on request ( please add RAL code after index number )

LED module: LED module included 2700K, 3000K or 4000K Colour temperature:

>80 in standard, other on request Colour Rendering Index

Driver: Electronic Integrated driver

Emergency unit: N/A Movement sensor: N/A Daylight control sensor: N/A

Operating temperature 0°C ... +40°C range:

IP20 in standard, IP44 on IP Class:

220-240V 50/60Hz Power: Lighting direction: Direct lighting White

Reflector type: Light distribution: Symmetric Diffuser: Microprismatic

General data: 5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance

+/- 10%.



