

NANO PARK



Wall mounted LED luminaire

- Mounting:** Wall recessed
- Body material:** Steel and aluminium
- Colour:** Standard White RAL 9016, other RAL colours on request (please add RAL code after index number)
- LED module:** LED module included
- Colour temperature:** 2700K
- Colour Rendering Index (CRI):** >80
- Driver:** Electronic driver included
- Emergency unit:** N/A
- Movement sensor:** N/A
- Daylight control sensor:** N/A
- Operating temperature range:** 0°C ... +40°C
- IP Class:** IP20
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct
- Reflector type:** N/A
- Light distribution:** Symmetric
- General data:** 3 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6516.140/830	140	3	3000	Ra > 80	30.000	3	3	0,40
6516.140/840	140	3	4000	Ra > 80	30.000	3	3	0,40

