

UNO FIX MINI



Recessed LED downlight for installation in suspended ceilings.

- Mounting:** Ceiling recessed, mounting brackets included
- Body material:** Aluminium
- Colour:** Standard Black RAL 9005, other RAL colours on request (please add RAL colour after index number)
- LED module:** Philips / Osram / Tridonic or equivalent LED module included
- Colour temperature:** 3000K or 4000K in standard other on request
- Colour Rendering Index (CRI):** >80 or >90 available
- Driver:** Electronic driver in standard, DALI or 1-10V Analogue on request
- Emergency unit:** N/A
- Movement sensor:** N/A
- Daylight control sensor:** N/A
- Operating temperature range:** 0°C ... +40°C
- IP Class:** IP20
- Power:** 220-240V 50/60Hz
- Lighting direction:** Direct lighting with possibility of light direction adjustment
- Reflector type:** Aluminium glossy
- Light distribution:** Symmetric
- Diffuser:** Clear or frosted glass on request
- General data:** 5 Years standard warranty
Different lumen output or wattage available on request
All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.
System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5878.1100/827	1100	9	2700	Ra > 80	50.000	5	3	1,30
5878.1100/830	1100	9	3000	Ra > 80	50.000	5	3	1,30
5878.1100/840	1100	9	4000	Ra > 80	50.000	5	3	1,30
5878.1100/927	1100	11	2700	Ra > 90	50.000	5	3	1,30
5878.1100/930	1100	11	3000	Ra > 90	50.000	5	3	1,30
5878.1100/940	1100	11	4000	Ra > 90	50.000	5	3	1,30

